BOXY WM 39

Features

- Solid Aluminium Body.
- Extra Safety Impact Resistant, Toughened Glass.
- High-Efficiency Optical System
- Extra Clear Glass To Increase Efficiency Of The Fixture
- High-Grade Silicon Gasket- Heat & Cold Resistant.
- “Coro Safe” High-Grade Anodizing
- “Duracoat” Double Layer Body Coating To WithStand Corrosion
- “Weatherprotect” Outdoor Rated Powder Coating
- “Long Life” Thermal Management.

Technical Data

Application Category	Wall Mount
Wattage	2.5W
Source Lumen	300lm
Ingress Protection	IP65
Material	Aluminium Extrusion And Solid Aluminiium Parts
Coatings	"Weather Protect"High Grade Pure Polyester Outdoor Powder Coating
Light Source	High Power Led
Life Span	50000 hrs*
Screws	Stainless Steel
Power Supply	230V AC
Gasket	High Grade Long Lasting Silicon Gasket.
Glass	High Grade PMMA Clear Diffuser.
Cable Gland	-
Power Cable	Cable Not Included
Dimension	Width : 39mm, Height :86mm
Gross Weight	-



FAMILY	TYPE	CODE	WATTAGE (LUMEN)	CRI	OPTICS	CC	FINISH	SUPPLY	ACCESSORIES
BOXY	WM	39	2.5 – 2.5W (300lm)	80 – 80 CRI	N – 12º M – 24º W – 40º WF – 60º	27 – 2700K 30 – 3000K 40 – 4000K	G – Grey DB – Dark Black MW – Matt White C – Corten DLG – Dark leaf Green	230 - 230V AC	HL

Code Example :- BOXY-WM-39-2.5-80-M-30-G-230-HL

IP 65 | CRI 80 | 230V AC

BOXY WM 39

Accessories

HL
(Hexcell Louvre)
Optional accessory that integrates to reduce glare.

Optional Accessories



IP Connectors
Straightrt Connector
IP Rating - IP68



IP Connectors
T Connector
IP Rating - IP68



IP Connectors
4 Way Connector
IP Rating - IP68

Finish

Grey

Dark Black

Dark Leaf Green



Matt White

Corten

Matt Black

Brown