

BULLET CM 61 D3


Features

- Solid Aluminium Body.
- Extra Safety Impact Resistant, Toughened Glass.
- High-Efficiency Optical System
- Extra Clear Glass To Increase Efficiency Of The Fixture
- High-Grade Silicon Gasket- Heat & Cold Resistant.
- “Coro Safe” High-Grade Anodizing
- “Duracoat” Double Layer Body Coating To WithStand Corrosion
- “Weatherprotect” Outdoor Rated Powder Coating
- “Long Life” Thermal Management.



Technical Data

Application Category	Wall Mount
Wattage	7W
Source Lumen	540lm
Ingress Protection	IP65
Material	Aluminium Extrusion And Solid Aluminium Parts
Coatings	"Weather Protect" High Grade Pure Polyester Outdoor Powder Coating
Light Source	High Power Led
Life Span	50000 hrs*
Screws	Stainless Steel
Power Supply	230V AC
Gasket	High Grade Long Lasting Silicon Gasket.
Glass	Extra Safety Impact Resistant, Toughened Glass.
Cable Gland	-
Power Cable	Cable Not Included
Dimension	Height :118mm, Dia:61mm
Gross Weight	-



FAMILY	TYPE	CODE	WATTAGE (LUMEN)	CRI	OPTICS	CC	FINISH	SUPPLY	ACCESSORIES
BULLET	CM	61-D3	7 – 7W (540lm)	80 – 80 CRI	N – 12° SP – 18° WF – 54°	27 – 2700K 30 – 3000K 40 – 4000K	G – Grey DB – Dark Black MW – Matt White C – Corten DLG – Dark leaf Green	230 - 230V AC	HL

Code Example :- BULLET-CM-61-D3-7-80-SP-30-G-230-HL



BULLET CM 61 D3

Accessories



HL
(Hexcell Louvre)
Optional accessory that
integrates to reduce glare.


Optional Accessories




IP Connectors
Straight Connector
IP Rating - IP68



IP Connectors
T Connector
IP Rating - IP68




IP Connectors
4 Way Connector
IP Rating - IP68



cnc
LIGHTING
BY
RKLITE
SINCE 1961


Finish




Grey



Dark Black



Dark Leaf
Green




Matt White



Corten



Matt Black



Brown