

### CIELO SP 118


#### **Features**

- Solid Aluminium Body.
- Extra Safety Impact Resistant, Toughened Glass.
- High-Efficiency Optical System
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- High Grade Silicon Gasket- Heat & Cold Resistant.
- High Grade Brass Nickel Plated German Gland.
- High Grade Neoprene Silicon Based Italian Cable To Withstand Any Weather Conditions.
- Recessed Spike Made Of GFR Polymer.
- "Coro Safe" High Grade Anodizing.
- "Duracoat" Double Layer Body Coating To With Stand Corrosion.
- "Weather protect" Outdoor Rated Powder Coating.
- "Capillary Protect System" Anti-Capillary System To Protect Any Water Ingress From Cable Joints.
- 1000mm All Weather Neoprene Silicon Power Cable Included



#### **Technical Data**

| Application Category | Projectors   |  |  |  |  |
|----------------------|--|--|--|--|--|
| Wattage              | 18W  |  |  |  |  |
| Source Lumen         | 1620lm   |  |  |  |  |
| Ingress Protection   | IP66   |  |  |  |  |
| Material             | Aluminium Extrusion And Solid Aluminium Parts                                      |  |  |  |  |
| Coatings             | "Duracoat" Double Layer Body Coating To WithStand Corrosion.                       |  |  |  |  |
| Light Source         | High Power Led   |  |  |  |  |
| Life Span            | 50000 hrs*   |  |  |  |  |
| Screws               | Stainless Steel  |  |  |  |  |
| Power Supply         | Constant Current Driver (27V, 700mA)   |  |  |  |  |
| Gasket               | High-Grade Silicon Gasket Heat and Cold Resistant High Transmission Tempered Glass |  |  |  |  |
| Glass                |  |  |  |  |  |
| Cable Gland          | German Gland   |  |  |  |  |
| Power Cable          | Cable Not Included   |  |  |  |  |
| Dimension            | Width: 83mm, Height: 80mm, Dia: 118mm  |  |  |  |  |
| Gross Weight         |  |  |  |  |  |



| FAMILY | TYPE | CODE | WATTAGE<br>(LUMEN)   | CRI         | OPTICS                                    | CCT                                    | FINISH  | SUPPLY  | ACCESSORIES          |
|--------|------|------|----------------------|-------------|---|--|---|---|----------------------|
| CIELO  | SP   | 118  | 18 – 18W<br>(1620lm) | 80 – 80 CRI | N – 12°<br>M – 24°<br>W – 40°<br>WF – 60° | 27 – 2700K<br>30 – 3000K<br>40 – 4000K | G – Grey DB – Dark Black MW – Matt White C – Corten DLG – Dark leaf Green | CC – Constant<br>Current Driver<br>(27V, 700mA) | HL<br>CL<br>TB<br>SP |

Code Example :- CIELO-SP-118-18-80-N-30-G-CC- HL



sales@cnclighting.in www.cnclighting.in



## CIELO SP 118

#### Accessories



HL ( Hexcell Louvre) Optional accessory that integrates to reduce glare.



CL (Cowl) Optional accessor



TB (Tree Belt) Optional accessory



SP (Spike) Optional accessory

# **Driver Options**



Brand - Meanwell Code - LPC-20-700 Type - Constant Current Watt - 25W IP Rating - IP54

IP Rating - IP54 No Of Fixtures - Min 1, Max 1 Dimension-84\*57\*29.5(L\*W\*H)

## **Optional Accessories**



IP Connectors Straing Connector IP Rating - IP68





IP Connectors T Connector IP Rating - IP68



IP Connectors 4 Way Connector IP Rating - IP68

### Finish



Dark Black











nite Corten Matt Black Brown