


### CIELO SP 64 COB


#### **Features**

- Solid Aluminium Body.
- Extra Safety Impact Resistant, Toughened Glass.
- High-Efficiency Optical System
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- High Grade Silicon Gasket- Heat & Cold Resistant.
- High Grade Brass Nickel Plated German Gland.
- High Grade Neoprene Silicon Based Italian Cable To Withstand Any Weather Conditions.
- Recessed Spike Made Of GFR Polymer.
- "Coro Safe" High Grade Anodizing.
- "Duracoat" Double Layer Body Coating To With Stand Corrosion.
- "Weather protect" Outdoor Rated Powder Coating.
- "Capillary Protect System" Anti-Capillary System To Protect Any Water Ingress From Cable Joints.
- 1000mm All Weather Neoprene Silicon Power Cable Included



#### **Technical Data**

Application Category	Projectors					
Wattage	9W 840lm					
Source Lumen						
Ingress Protection	IP66					
Material	Aluminium Extrusion And Solid Aluminium Parts					
Coatings	"Duracoat" Double Layer Body Coating To WithStand Corrosion.					
Light Source	High Power Led					
Life Span	50000 hrs*					
Screws	Stainless Steel					
Power Supply	Constant Current Driver (36V, 250mA)					
Gasket	High-Grade Silicon Gasket Heat and Cold Resistant					
Glass	High Transmission Tempered Glass					
Cable Gland	German Gland					
Power Cable	Cable Not Included					
Dimension	Width: 98mm, Height: 75mm, Dia: 64mm					
Gross Weight						



FAMILY	TYPE	CODE	WATTAGE (LUMEN)	CRI	OPTICS	ССТ	FINISH	SUPPLY	ACCESSORIES
CIELO	SP	64COB	9 – 9W (840lm)	80 – 80 CRI	SP – 16° M – 27° W – 38°	27 – 2700K 30 – 3000K 40 – 4000K	G – Grey DB – Dark Black MW – Matt White C – Corten DLG – Dark leaf Green	CC – Constant Current Driver (36V, 250mA)	HL CL TB SP

Code Example :- CIELO-SP-64COB-9-80-SP-30-G-CC- HL



sales@cnclighting.in www.cnclighting.in



## CIELO SP 64 COB

#### Accessories



HL ( Hexcell Louvre) Optional accessory that integrates to reduce glare.



CL (COWI)



TB (Tree Belt) Optional accessory



SP (Spike) Optional accessory

# **Driver Options**



Brand - Fulham Code - T12400250-10P10 Type - Constant Current Watt - 10W IP Rating - IP66

No Of Fixtures - Min 1, Max 1 Dimension- 81\*41\*31mm(L\*W\*H)

## **Optional Accessories**



IP Connectors Straing Connector IP Rating - IP68





IP Connectors T Connector IP Rating - IP68



IP Connectors 4 Way Connector IP Rating - IP68

### Finish



Dark Black











sales@cnclighting.in www.cnclighting.in