

PYXIS


Features

- Bollards Designs That Blends With The Modern City Landscapes To Provide A More Homogeneous And Distinguished Look
- Designs That Affects The Lighting Output, And There Are Other Parameters Like Mounting Height, Spacing, Outreach
- High-Efficiency Led Technology Provides Maximum Flexibility For Applications Such As Gardens, Landscape, Pathways or Walkways.
- Corrosion Resistant Double Layer Polyester Powder Coated Paint Finish Die Cast/ Extruded Aluminium Housing/Gi Pipes
- Stainless Steel Screws And Silicone Gaskets. The power Unit Is Built In
- Thermal-Shock Resistant Tempered Glass. .
- Operating Temperature: -20°C ~ +55°C
- Outstanding Light Efficiency And Integrates Itself Through The Reduced Design Into Historic And Modern Surroundings.
- Both Its Appearance And The Materials Used In Its Manufacture Are Intended To Last.



Technical Data

Application Category	Bollard					
Wattage	4W					
Source Lumen	400lm					
Ingress Protection	IP65					
Material	Aluminium Extrusion And Solid Aluminiium Parts					
Coatings	"Weather Protect" High Grade Pure Polyester Outdoor Powder Coating					
Light Source	High Power Led					
Life Span	50000 hrs*					
Screws	Stainless Steel					
Power Supply	230V AC					
Gasket	High Grade Long Lasting Silicon Gasket.					
Glass	High Grade PMMA Clear Diffuser.					
Cable Gland	-					
Power Cable	Cable Not Included					
Dimension	Width - 120 mm, Height - 600mm					
Gross Weight	•					



DLG - Dark leaf Green

FAMILY	TYPE	CODE	WATTAGE (LUMEN)	CRI	OPTICS	CC	FINISH	SUPPLY	ACCESSORIES
PYXIS	ВО	45 - 450 60 - 600	4 – 4W (400lm)	80 – 80 CRI	ASY – Asymmetric	27 – 2700K 30 – 3000K	G – Grey DB – Dark Black MW – Matt White C – Corten	230 - 230V AC	АВК

Code Example :- PYXIS-BO-60-4-80-ASY-30-G-230-ABK



sales@cnclighting.in www.cnclighting.in



PYXIS

Accessories



ABK
(Anchor Bolt Kit)
Provided with the fixture for installation.

Optional Accessories



Finish



sales@cnclighting.in www.cnclighting.in