

TERRA ING 140 ASY


Features

- Excellent Corrosion Resistant Low Copper Solid Aluminum Body
- SS316 Faceplate
- Extra Safety Impact Resistant, Toughened Glass
- Extra Clear Glass To Increase Efficiency of the Fixture
- High-Grade Silicon Gasket Heat and Cold Resistant
- High-Grade Brass Nickel Plated IP68 German Gland
- High-Efficiency Optical System
- Multiple Accessories Support
- Cree LED 50000* Hrs Life
- Recessed Housing Made of GFR Polymer
- Coro Safe High-Grade Anodizing
- Capillary Protect System Anti Capillary System To Protect Any Water Ingress From Cable Joints.
- Long Life Thermal Management



Technical Data

Application Category	Inground				
Wattage	6W/8W				
Source Lumen	540lm/720lm				
Ingress Protection	IP67				
Material	Excellent Corrosion Resistance Low Copper, Solid Aluminium Body.				
Coatings	Coro Safe High-Grade Anodizing.				
Light Source	High Power Led				
Life Span	50000 hrs*				
Screws	Stainless Steel				
Power Supply	CC - Constant Current Driver (12V, 500mA/700mA)/ CV- 24V DC				
Gasket	High-Grade Silicon Gasket Heat and Cold Resistant				
Glass	HIgh Transmission Tempered Glass				
Cable Gland	German Gland				
Power Cable	Cable Not Included				
Dimension	Width: 140mm, Height: 88mm, Dia: 123mm				
Gross Weight					



FAMILY	TYPE	CODE	WATTAGE (LUMEN)	CRI	OPTICS	CCT	FINISH	SUPPLY	ACCESSORIES
TERRA	ING	140-ASY	6– 6W (540lm) 8– 8W (720lm)	80 – 80 CRI	ASY – Asymmetric EL – 20x40°	27 – 2700K 30 – 3000K 40 – 4000K	SS – Stainless Steel 316	CC – Constant Current Driver (12V, 500/700mA) CV - 24V DC	RH

Code Example :- TERRA-ING-140-ASY-6-80-ASY-30-SS-CC-RH



sales@cnclighting.in www.cnclighting.in



TERRA ING 140 ASY

Accessories



RH (Recessed Housing) Provided with the fixture for installation.

Driver Options



Brand- Meanwell Code- APC-25-500 Type - Constant Current

Watt - 25W IP Rating - IP54

No Of Fixtures - Min 2, Max 4 Dimension-84*57*29.5(L*W*H)



Brand- Meanwell Code- APC-25-700 Type - Constant Current

Watt - 25W IP Rating - IP54

No Of Fixtures - Min 1, Max 1 Dimension-84*57*29.5(L*W*H)

Optional Accessories



IP Connectors Straight Connector IP Rating - IP68





IP Connectors T Connector IP Rating - IP68



IP Connectors 4 Way Connector IP Rating - IP68

Finish



Stainless Steel

sales@cnclighting.in www.cnclighting.in