

TERRA ING 55


Features

- Excellent Corrosion Resistant Low Copper Solid Aluminum Body
- SS316 Faceplate
- Extra Safety Impact Resistant, Toughened Glass
- Extra Clear Glass To Increase Efficiency of the Fixture
- High-Grade Silicon Gasket Heat and Cold Resistant
- High-Grade Brass Nickel Plated IP68 German Gland
- High-Efficiency Optical System
- Multiple Accessories Support
- Cree LED 5000* Hrs Life
- Recessed Housing Made of GFR Polymer
- Coro Safe High-Grade Anodizing
- Capillary Protect System Anti Capillary System To Protect Any Water Ingress From Cable Joints.
- Long Life Thermal Management



Technical Data

| Application Category | Inground | | | | | | |
|----------------------|-----------------------------------------------------------------|--|--|--|--|--|--|
| Wattage | 1.5W / 2W | | | | | | |
| Source Lumen | 180lm/ 240lm | | | | | | |
| Ingress Protection | IP67 | | | | | | |
| Material | Excellent Corrosion Resistance Low Copper, Solid Aluminium Body | | | | | | |
| Coatings | Coro Safe High-Grade Anodizing. | | | | | | |
| Light Source | 1 x High Power Led | | | | | | |
| Life Span | 50000 hrs* | | | | | | |
| Screws | Stainless Steel | | | | | | |
| Power Supply | CC - Constant Current Driver (3V, 500mA/ 700mA)/ CV- 24V DC | | | | | | |
| Gasket | High-Grade Silicon Gasket Heat and Cold Resistant | | | | | | |
| Glass | High Transmission Tempered Glass | | | | | | |
| Cable Gland | German Gland | | | | | | |
| Power Cable | Cable Not Included | | | | | | |
| Dimension | Width: 55mm, Height: 69/90mm, Dia: 52mm | | | | | | |
| Gross Weight | - | | | | | | |



| FAMILY | TYPE | CODE | WATTAGE (LUMEN) | CRI | OPTICS | ССТ | FINISH | SUPPLY | ACCESSORIES |
|--------|------|------|--------------------------------------------|-------------|---------------------------------------------------------------------------|----------------------------------------|-----------------------------|---------------------------------------------------------------------|----------------|
| TERRA | ING | 55 | 1.5 – 1.5W (180lm) 2 – 2W (240lm) | 80 – 80 CRI | N – 12° M – 24° W – 40° WF – 60° EL - 20x40° DF – Diffused | 27 – 2700K 30 – 3000K 40 – 4000K | SS – Stainless Steel 316 | CC – Constant Current Driver (3V, 500mA/700mA) CV - 24V DC | HL RH GC |

Code Example :- TERRA-ING-55-1.5-80-N-30-SS-CC-GC



sales@cnclighting.in www.cnclighting.in



TERRA ING 55

Accessories



HL (Hexcell Louvre) Optional Accessory



GC (Glare Control Glass) Optional accessory



RH (Recessed Housing) Provided with the fixture for installation.

Driver Options



Brand- Meanwell Code- LPHC-18-350 Type - Constant Current Watt - 18W

IP Rating - IP67 No Of Fixtures - Min 3, Max 14 Dimension-140*30*22(L*W*H)



Brand- Meanwell Code- APC-25-500 Type - Constant Current Watt - 25W

IP Rating - IP54 No Of Fixtures - Min 6, Max 16 Dimension-84*57*29.5(L*W*H)



Brand- Meanwell Code- LPV-20-24

Type - Constant Voltage 24V DC

Watt - 20W IP Rating - IP67

No Of Fixtures - Min 1, Max 4 Dimension-118*35*26mm (L*W*H)

Optional Accessories



IP Connectors Straight Connector IP Rating - IP68





IP Connectors T Connector IP Rating - IP68



IP Connectors 4 Way Connector IP Rating - IP68

Finish



Stainless Steel

sales@cnclighting.in www.cnclighting.in